

SA2

Serial Communications Board



DESCRIPTION

The SA2 is a high-speed serial adapter designed to work together with the XCHANGER.NET codec software.

APPLICATIONS

- In distributed TCP/IP sound installations coupled with the XCHANGER.NET Windows™ client-server software.
- In specialized serial control applications.

FEATURES

- 2 asynchronous serial interfaces and a Centronics-style port
- Fully RF filtered
- Port 1/2 available as an EIA-422 (V.11) style or EIA-485 style interface
- 2.5Mbps maximum speed
- Conforms to EN 55103 according to 89/336/EMC

SPECIFICATIONS

BUS	PCI
Serial ports	2
Parallel ports	1
Maximum speed	2.5Mbps
Interface	1xEIA 485/422 + 1xEIA-232
Connector	DB-25
Physical	1 PCI slot
Weight	150 g
Power supply	PC-supplied ±12V, +5V
Operating temp.	0-40°C
Versions	/A EIA485+EIA485 /B EIA485+EIA422 /C EIA422+EIA422

SA2 V1.11 / 2003-11-12

Specifications may change without prior notice.
Copyright © by Acutron 2002-2003 all rights reserved.
Acutron® is a trademark of Acutron
Windows is a trademark of Microsoft Corp.

ABC-Abrunheira Business Center
Edifícios 10-11 R. das Maçarocas
Abrunheira 2710-056 Sintra
Tel +351 219152040
Fax +351219154079
web: www.acutron.net
mail: info@autron.net

DISTRIBUTOR



Acutron



digital audio