
Acutron Electroacustica Lda

SHAPER

Digital 4-Band Parametric Equalizer/Limiter





ACUITON BILLION AND BUILD



The SHAPER Equalizer/Dynamics Controller is used to recover subjectively unsuitable signals, to correct for room acoustics and also to constrain an incoming signal which dynamic range does not fit the transmission or recording media limitations.

APPLICATIONS

☐ In PA systems where the audio signal must be equalized and band-limited

☐ As a general-purpose processor

FEATURES

■ 48kHz professional sample rate

☐ Fully RF filtered

■ Automatic bypass on power loss

□ All I/O is balanced

□ DSP-driven with robust V.11/V.28 communications

☐ Configuration (up to 13 presets) and ID kept in FLASH

non-volatile memory

☐ Units may be as far as 1200m from controller in the EIA-

485/V.11 interface case

☐ Microphone as well as line input

□ 24-bit converter/16-bit processing

☐ Fully EEC 55103 compliant according to 89/336/EMC

☐ Programmable threshold for limiter section

☐ 4-band Equalizer and high/low cut filters built-in

☐ Individual equalizer settings for each channel

☐ LCD display and keyboard for simplified programming

Includes a Windows™ 32-bit 98/NT/2000/XP configuration application, controlling the device through an EIA-232 interface (EIA-485/V.11 using a SA2 board, not

supplied)

SPECIFICATIONS

Conversion 24bit

Freq. response 20Hz-22kHz ±1.5dB

Sample rate 48kHz Noise <-75dBA

>40dB, 20Hz-20kHz **CMRR** THD+N <0.15% 20-10kHz Crosstalk >70dB 1kHz (>55dB 20kHz)

Dynamic range >85dB Overload level +10 dBu

100kΩ balanced Input Impedance **Output Impedance** 600Ω balanced

Equalizer

Bands

Equalizer ±12dB Q=1-16 Center Frequency 200-16kHz

Band-limit filters 100-400Hz, 4-20kHz

Limiter

-36/0dBu **Threshold** Attack 2mS Hold 2s Release 5s

19" rack, 1U **Physical** 350mm depth

3.0 Kg


Weight

115/230VA @ 5VA Power supply

Operating temp. 0-40°C

SHAPER V1.11 2003-11-13

Specifications may change without prior notice Copyright © by Acutron 2001-2003 all rights reserved. Acutron® is a trademark of Acutron Electroacustica Windows is a trademark of Microsoft Corp.



Edifícios 10-11 R. das Maçarocas Abrunheira 2710-056 Sintra Tel +351 21915204 Fax +3512191 web: www.acutron.net mail: info@autron.net

DISTRIBUTOR



